

## Tabriz Petrochemical Co.

### Styrene Monomer

#	Property	Units	Test Method	Value
1	Purity	Wt%	ASTM D-5135	99.7 min
2	Color (PT-CO) Scale	--	ASTM D-1209	10 max
3	Polymers	ppm wt	ASTM D-2121	10 max
4	Inhibitor (AS TBC)	ppm wt	ASTM D-4590	15 max
5	Aldehyde (AS BENZALDEHYDE )	ppm wt	ASTM D-2119	100 max
6	Peroxide (AS H202)	ppm wt	ASTM D-2340	50 max
7	Total Sulphur (AS "S")	ppm wt	ASTM D-3120	5 max
8	Ethyl-Benzene	ppm wt	ASTM D-5135	1000 max

Shipping : Bulk Carrier

### C7-C9

#	Property	Units	Test Method	Value
1	Sp.Gr @ ( 60/60°F )	---	---	0.7 - 0.9
2	R.V.P	Psia	---	10 max
3	I.B.P	°C	---	100 min
4	F.B.P	°C	---	165 max

Shipping : Bulk Carrier

### Cracked Fuel Oil ( C.F.O )

#	Property	Units	Test Method	Value
1	Sp.Gr.@ ( 15°C )	--	IP 189 , 190	1 - 1.3
2	Viscosity @ ( 100°C )	Cst	ASTM D-445	8 - 20
3	Flash Point	°C	ASTM D-93	70 min

Shipping : Bulk Carrier

### Crude Fuel Oil ( C9 + CUT )

#	Property	Units	Test Method	Value
1	Sp.Gr. 15°C	--	ASTM D-1298	0.85 - 1
2	Flash Point	°C	ASTM D-93	45 min
3	Pour Point	°C	ASTM D-97	<0

Shipping : Bulk Carrier